



BOXY 2 L HE 92740 DIM8

10748 9238 B-B



AVAILABLE IN

BLACK-BLACK 10748 9238 B-B

BLACK-FLEMISH BRONZE 10748 9238 B-FBR

BLACK-FLEMISH GOLD 10748 9238 B-FG

WHITE-WHITE 10748 9238 W-W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	LENS WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	LCA
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm)
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1810lm // 12W // 150lm/W
LED TECHNICS (LUMINAIRE)	1526lm // 13,8W // 111lm/W
Remarks	

High Efficacy : > 100lm/W

For detailed installation instructions, please consult the manual : [10748_XXX8_HAND.pdf](#)

DELTALIGHT

BOXY 2 L HE 92740 DIM8

10748 9238 B-B

Notes: