
DELTALIGHT




LUNELLE 52 SPM20 93030 MDL

REFERENCE 32820 9320 BRA

AVAILABLE IN
BRUSHED ALU 32820 9320 BRA
BRUSHED ALU-BLACK 32820 9320 BRA-B
BRUSHED ALU-WHITE 32820 9320 BRA-W
BRUSHED ANTHRACITE 32820 9320 BRAT
BRUSHED ANTHRACITE-BLACK 32820 9320 BRAT-B
BRUSHED ANTHRACITE-WHITE 32820 9320 BRAT-W
BRUSHED BROWN BRONZE 32820 9320 BRBB
BRUSHED BROWN BRONZE BLACK 32820 9320 BRBB-B
BRUSHED BROWN BRONZE WHITE 32820 9320 BRBB-W
BRUSHED COPPER 32820 9320 BRCU
BRUSHED COPPER-BLACK 32820 9320 BRCU-B
BRUSHED COPPER-WHITE 32820 9320 BRCU-W
BRUSHED GOLD 32820 9320 BRG
BRUSHED GOLD-BLACK 32820 9320 BRG-B
BRUSHED GOLD-WHITE 32820 9320 BRG-W
BRUSHED OLD BRONZE 32820 9320 BROB
BRUSHED OLD BRONZE-BLACK 32820 9320 BROB-B
BRUSHED OLD BRONZE-WHITE 32820 9320 BROB-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 / 3000K / 519lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	519lm // 5,6W // 92lm/W
LED TECHNICS (LUMINAIRE)	415lm // 6,4W // 64lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

VISOR 52

DELTALIGHT


LUNELLE 52 SPM20 93030 MDL

32820 9320 BRA

For detailed installation instructions, please consult the manual : **32820_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Light altering devices



32810 0010 DC VISOR 52 DC ☐

Notes: