





## SPY 52 93030 ADM SLIM

19836 9340 W

AVAILABLE IN  
**BLACK** 19836 9340 B  
**WHITE** 19836 9340 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Mains voltage track Mains voltage track mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.4
<b>ADJUSTABILITY</b>	0° to 90° swiveling, 360° rotatable
<b>INFORMATION</b>	REFLECTOR FL-30° 3F MULTI POWER SLIM ADAPTER 350-700mA Current selection via jumper on adapter Optional REFLECTORS 20° & 45° available

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	@ 700mA: LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm Or @ 500mA: LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm Or @ 350mA: LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
<b>TM-30 VALUES</b>	@ 700mA: rf: 90 / Rg: 99 @ 500mA: rf: 90 / Rg: 99 @ 350mA: rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	30°
<b>LED TECHNICS (LIGHT SOURCE)</b>	@ 700mA: 1467lm // 12,4W // 118lm/W Or @ 500mA: 1089lm // 8,6W // 127lm/W Or @ 350mA: 787lm // 5,8W // 135lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	@ 700mA: 936lm // 14,3W // 66lm/W Or @ 500mA: 695lm // 9,9W // 70lm/W Or @ 350mA: 502lm // 6,7W // 75lm/W

# DELTALIGHT

## SPY 52 93030 ADM SLIM

19836 9340 W

### Requirements

---

SPY 52 TUBE  
TRACK 3F DIM

### Accessories

---


HONEYCOMB 42  
SPREAD LENS 42  
LINEAR SPREAD LENS 42  
SOFTENING LENS 42  
GLASS SBL 42

For detailed installation instructions, please consult the manual : [19836\\_XXX0\\_HAND.pdf](#)


## FINISH YOUR SPECIFICATION

### Light altering devices


---




**19810 0010 B** HONEYCOMB 42 SINGLE USE B




**19810 0020** LINEAR SPREAD LENS 42




**19810 0030** SPREAD LENS 42



**19810 0040** SOFTENING LENS 42



**19810 0050** GLASS SBL 42



**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

# DELTALIGHT

## SPY 52 93030 ADM SLIM

19836 9340 W

### Finish your product



**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG


**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

### Replaceable reflector / lens



**19810 0180** SPY 52 REFLECTOR 20°



**19810 0190** SPY 52 REFLECTOR 45°



**19810 0240** SPY 52 REFLECTOR 30°

## COMPATIBLE TRACKS

### TRACK 3F DIM H

#### Available Colours

**200 14 410** TRACK 3F DIM H 1m

1000 m 1.6 kg



**200 14 420** TRACK 3F DIM H 2m

2000 m 3.2 kg



**200 14 430** TRACK 3F DIM H 3m

3000 m 4.8 kg



### TRACK 3F DIM IN

#### Available Colours

**200 13 410** TRACK 3F DIM IN 1m

1000 m 1.2 kg



# DELTALIGHT

## SPY 52 93030 ADM SLIM

19836 9340 W

**200 13 420** TRACK 3F DIM IN 2m

2000 m 2.4 kg



**200 13 430** TRACK 3F DIM IN 3m

3000 m 3.5 kg



### TRACK 3F DIM ON

#### Available Colours

**200 12 410** TRACK 3F DIM ON 1m

1000 m 1.1 kg



**200 12 420** TRACK 3F DIM ON 2m

2000 m 2.1 kg



**200 12 430** TRACK 3F DIM ON 3m

3000 m 3.1 kg



Notes: