



MINIGRID ON 250 SOFT 93045 DIM8

100088 9038 B-B



AVAILABLE IN

BLACK-BLACK 100088 9038 B-B

BLACK-WHITE 100088 9038 B-W

WHITE-BLACK 100088 9038 W-B

WHITE-WHITE 100088 9038 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	2 x REFLECTOR FL-45° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	831lm // 11,7W // 71lm/W

For detailed installation instructions, please consult the manual : [100088_XXX8_HAND.pdf](#)

Notes:

DELTALIGHT

MINIGRID ON 250 SOFT 93045 DIM8

100088 9038 B-B