
DELTALIGHT




INFORM ST 1380 92767

REFERENCE 25503 9220 W-B

AVAILABLE IN
BLACK-BLACK 25503 9220 B-B
BLACK-FLEMISH GOLD 25503 9220 B-FG
WHITE-BLACK 25503 9220 W-B
WHITE-WHITE 25503 9220 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 38 x 1393
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 500/750mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,6-27,9W / CRI>90 (R9: 50) / 2700K / 2532-3660lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	3660lm // 27,9W // 131lm/W
LED TECHNICS (LUMINAIRE)	3195lm // 32,1W // 100lm/W

Requirements

INFORM POWER SUPPLY 45W

For detailed installation instructions, please consult the manual : **25503_XXX0_HAND.pdf**

DELTALIGHT

INFORM ST 1380 92767

25503 9220 W-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Wood**	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



25510 0385 INFORM POWER SUPPLY 45W DIM5 — 1

Dimtype: DALI



25510 0430 INFORM POWER SUPPLY 45W — 1

Dimtype: non-dimmable

Notes: