
DELTALIGHT




DEEP RINGO OK LED 93033

REFERENCE 19435 9320 BRCU

AVAILABLE IN
NOIR 19435 9320 B
ALU BROSSÉ 19435 9320 BRA
ANTHRACITE BROSSÉ 19435 9320 BRAT
BRONZE BRUN BROSSÉ 19435 9320 BRBB
CUIVRE BROSSÉ 19435 9320 BRCU
OR BROSSÉ 19435 9320 BRG
BRONZE VIEUX BROSSÉ 19435 9320 BROB
CRÈME 19435 9320 CR
FLEMISH BRONZE 19435 9320 FBR
FLEMISH GOLD 19435 9320 FG
COULEUR OR 19435 9320 GC
BLANC 19435 9320 W





View on website

General info	
LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 76
RECESSED DEPTH (MM)	100
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 30° inclinable, 360° rotatif
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, EPD, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm
RVALUES	Rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	723lm // 10W // 73lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

DEEP RINGO OK LED 93033

19435 9320 BRCU


For detailed installation instructions, please consult the manual : **19435_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Stucanet**	-
 **Wood**	-
 **Concrete**	-
 **Concrete + plaster**	-
 **Lintel + plaster**	-
 **Hollow-core slab**	-
 **Hollow-core slab + plaster**	-
 **Stretched ceiling**	-

FINISH YOUR SPECIFICATION

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DELTALIGHT


DEEP RINGO OK LED 93033

19435 9320 BRCU

les alimentations led		# of Fixtures
web2print_power_supply_info_box		Min current | Max current
	**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 **Dimtype: 1 à 10 V** **Cutout dimension (mm): 30**	1
	**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 **Dimtype: DALI** **Cutout dimension (mm): 45**	1
	**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL **Dimtype: non dimmable** **Cutout dimension (mm): 30**	1
	**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL **Dimtype: WDL = dimmable sans fil** **Cutout dimension (mm): 45**	1
	**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 **Dimtype: 1 à 10 V** **Cutout dimension (mm): 30**	1
	**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 **Dimtype: DALI** **Cutout dimension (mm): 45**	1
	**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL **Dimtype: non dimmable** **Cutout dimension (mm): 30**	1
	**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL **Dimtype: WDL = dimmable sans fil** **Cutout dimension (mm): 45**	1
	**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 **Dimtype: fin de phase ou bouton poussoir** **Cutout dimension (mm): 56**	2 | 2

DEEP RINGO OK LED 93033


19435 9320 BRCU



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 4(4) | 4(4)

Dimtype: 1 à 10 V ou DALI ou boutton poussoir


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 2(1) | 2(1)


Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 2


Dimtype: 1 à 10 V ou DALI ou boutton poussoir



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 2(2) | 2(1)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 2->6(6) | 6(4)

Dimtype: 1 à 10 V ou DALI ou boutton poussoir


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 3(2) | 2(1)

Dimtype: 1 à 10 V ou bouton poussoir


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 2(2) | 2(1)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 3->3 | 2->3

Dimtype: non dimmable


Cutout dimension (mm): 90



21012 004W LED POWER SUPPLY MULTI-POWER WDL 3(3) | 3(3)

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 3 | 3


Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 54

DELTALIGHT

DEEP RINGO OK LED 93033


19435 9320 BRCU



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 — 1

Dimtype: fin de phase


Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 — 1

Dimtype: fin de phase


Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 — 2->3

Dimtype: fin de phase


Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 2 | 2

Dimtype: fin de phase


Cutout dimension (mm): 48



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 2(2)

Dimtype: non dimmable


Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 — 2(1)

Dimtype: non dimmable


Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 30



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 30

Notes: