



OML50 - INFORM DU HO 1640mm 8+8LED 93063

31435 9330 B

BESCHIKBAAR IN
ZWART 31435 9330 B



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.4
INFO	CLUSTER DOWN: 2131lm/m CLUSTER UP: 2663lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	E
CERTIFICATEN	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm UP: LED cluster 30,2W / CRI>90 (R9: 50) / 3000K / 4368lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 3494lm // 24,2W // 145lm/W UP: 4368lm // 30,2W // 145lm/W

Notes: