



SPY 52 CLIP SOFT 93020

19898 9020 W-W

AVAILABLE IN

NOIR-NOIR 19898 9020 B-B


FLEMISH BRONZE-NOIR 19898 9020 FBR-B

FLEMISH GOLD-NOIR 19898 9020 FG-B

ENTIÈREMENT BLANC 19898 9020 FW

COULEUR OR-NOIR 19898 9020 GC-B

BLANC-BLANC 19898 9020 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Semi-encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	REFLECTOR FL-20° EXCLDIMMABLE LED POWER SUPPLY 500mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	650lm // 11,7W // 55lm/W

Requirements

SPY 52 TUBE

LED POWER SUPPLY 500mA-DC DIM

Options

MOUNTING KIT FLUSH SPY

Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42

SOFTENING LENS 42

DELTALIGHT

SPY 52 CLIP SOFT 93020

19898 9020 W-W

GLASS SBL 42

For detailed installation instructions, please consult the manual : [19898_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Plasterboard	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Stucanet	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Wood	-
 Concrete	-
 Concrete + plaster	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Lintel + plaster	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Hollow-core slab	-
 Hollow-core slab + plaster	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Stretched ceiling	-




FINISH YOUR SPECIFICATION

les alimentations led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current

DELTALIGHT










SPY 52 CLIP SOFT 93020

19898 9020 W-W

	<u>300 48 500 ED1</u>	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	2	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	<u>300 48 500 ED5</u>	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2	☐
	Dimtype: DALI			
	Cutout dimension (mm): 45			
	<u>300 48 500 MDL</u>	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	2	☐
	Dimtype: non dimmable			
	Cutout dimension (mm): 30			
	<u>300 48 500 WDL</u>	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	2	☐
	Dimtype: WDL = dimmable sans fil			
	Cutout dimension (mm): 45			
	<u>300 90 61</u>	LED POWER SUPPLY MULTI-POWER DIM6	2	☐
	Dimtype: fin de phase ou bouton poussoir			
	Cutout dimension (mm): 56			
	<u>300 90 63</u>	LED POWER SUPPLY MULTI-POWER DIM9	3(3)	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir			
	Cutout dimension (mm): 82			
	<u>300 90 64</u>	LED POWER SUPPLY MULTI-POWER DIM7	2(1)	☐
	Dimtype: 1 à 10 V ou bouton poussoir			
	Cutout dimension (mm): 72			
	<u>300 90 68</u>	LED POWER SUPPLY MULTI-POWER DIM5	2(1)	☐
	Dimtype: DALI			
	Cutout dimension (mm): 72			
	<u>300 90 69</u>	LED POWER SUPPLY MULTI-POWER HV DIM9	5(3)	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir			
	Cutout dimension (mm): 84			
	<u>300 90 124</u>	LED POWER SUPPLY MULTI-POWER DIM7	1(1)	☐
	Dimtype: 1 à 10 V ou bouton poussoir			
	Cutout dimension (mm): 55			

SPY 52 CLIP SOFT 93020

19898 9020 W-W


	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1) ☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	2 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	2 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	2 ☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	3(3) ☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	2 ☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 ☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	1 ☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2 ☐

DELTALIGHT

SPY 52 CLIP SOFT 93020

19898 9020 W-W

kit de montage



414 90 01 MOUNTING KIT FLUSH SPY


☐

Cutout dimension (mm): 83


modifier les dispositifs de lumière



19810 0010 B HONEYCOMB 42 SINGLE USE B

☐


19810 0020 LINEAR SPREAD LENS 42

☐


19810 0030 SPREAD LENS 42

☐

19810 0040 SOFTENING LENS 42

☐


19810 0050 GLASS SBL 42

☐

19810 0060 B HONEYCOMB 42 DOUBLE USE B

☐

Terminez votre produit



19810 0100 B SPY 52 TUBE B

☐




DELTALIGHT

SPY 52 CLIP SOFT 93020

19898 9020 W-W

19810 0100 FBR	SPY 52 TUBE FBR	☐
19810 0100 FG	SPY 52 TUBE FG	☐
19810 0100 GC	SPY 52 TUBE GC	☐
19810 0100 W	SPY 52 TUBE W	☐

Réflecteur / lentille remplaçable

	19810 0180	SPY 52 REFLECTOR 20°	☐
	19810 0190	SPY 52 REFLECTOR 45°	☐
	19810 0240	SPY 52 REFLECTOR 30°	☐

Notes: