



MULTINOVA 55 OK 400 930 DIM4



28022 9304 W

AVAILABLE IN

NOIR 28022 9304 B

COULEUR OR 28022 9304 GC

BLANC 28022 9304 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	8.5
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	INCL.PC SBL ADJUSTABLE 0-90°/355° INCL.DIMMABLE LED POWER SUPPLY

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI ou DSI ou bouton poussoir
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm
RVALUES	Rf: 89 / Rg: 97
SDMC	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	4767lm // 34,4W // 139lm/W
LED TECHNICS (LUMINAIRE)	3842lm // 39,6W // 97lm/W




Options

COVERSET R 62-90-100

For detailed installation instructions, please consult the manual : [28022_XXX4_HAND.pdf](#)

FINISH YOUR SPECIFICATION

les sets pour recouvrement plafond

	<u>204 00 62 ANO</u> COVERSET R 62 ANO	☐
	<u>204 00 62 B</u> COVERSET R 62 B	☐
	<u>204 00 62 W</u> COVERSET R 62 W	☐
	<u>204 00 90 ANO</u> COVERSET R 90 ANO	☐
	<u>204 00 90 B</u> COVERSET R 90 B	☐
	<u>204 00 90 W</u> COVERSET R 90 W	☐
	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐

Notes: