



INFORM SQ P475-9 DOWN-UP 93067

25573 9320 B-B



AVAILABLE IN

BLACK-BLACK 25573 9320 B-B

BLACK-FLEMISH GOLD 25573 9320 B-FG

WHITE-BLACK 25573 9320 W-B

WHITE-WHITE 25573 9320 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.2
ADJUSTABILITY	non adjustable
INFORMATION	108 x REFLECTOR FL-67° (DOWN) EXCL.LED POWER SUPPLY 900mA-DC (DOWN) - 1200mA (UP) INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 4 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: 3 x (LED cluster 10,5W / CRI>90 (R9: 50) / 3000K / 1602lm) UP: 6 x (LED cluster 7W / CRI>90 (R9: 50) / 3000K / 1068lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 4806lm // 31,5W // 152lm/W UP: 6408lm // 42W // 152lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 4075lm // 36,2W // 113lm/W UP: 4319lm // 48,3W // 89lm/W

Requirements

INFORM POWER SUPPLY 100W
INFORM SQ POWERBOX L 85W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [25573_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐



LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current	
	25510 0385 INFORM POWER SUPPLY 45W DIM5	only UP or only DOWN	☐
Dimtype: DALI			
	25510 0415 INFORM POWER SUPPLY 100W DIM5	1	☐
Dimtype: DALI			

INFORM SQ P475-9 DOWN-UP 93067

25573 9320 B-B


	25510 0430 INFORM POWER SUPPLY 45W	only UP or only DOWN ☐
Dimtype: non-dimmable		
	25510 0460 INFORM POWER SUPPLY 100W	1 ☐
Dimtype: non-dimmable		

Power box



of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

	25510 0475 B INFORM SQ POWERBOX L 85W DIM5 B	1 ☐
Dimtype: DALI		
	25510 0475 W INFORM SQ POWERBOX L 85W DIM5 W	1 ☐





Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐


DELTALIGHT

INFORM SQ P475-9 DOWN-UP 93067

25573 9320 B-B

	204 00 100 ANO COVERSET R 100 ANO	☐
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐
	204 62 62 ANO COVERSET S 62 ANO	☐
	204 62 62 B COVERSET S 62 B	☐
	204 62 62 W COVERSET S 62 W	☐
	204 80 80 ANO COVERSET S 80 ANO	☐
	204 80 80 B COVERSET S 80 B	☐
	204 80 80 W COVERSET S 80 W	☐
	204 90 90 ANO COVERSET S 90 ANO	☐
	204 90 90 B COVERSET S 90 B	☐
	204 90 90 W COVERSET S 90 W	☐


Suspension parts

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		

DELTALIGHT

INFORM SQ P475-9 DOWN-UP 93067

25573 9320 B-B



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: