
DELTALIGHT




M26L - HALOSCAN HP SOFT 93014 MDL

REFERENCE 23131 9010 B

AVAILABLE IN
BLACK 23131 9010 B
WHITE 23131 9010 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS SP-14° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,8W / CRI>90 (R9: 50) / 3000K-1800K / 1307lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	1307lm // 11,8W // 110lm/W
LED TECHNICS (LUMINAIRE)	1062lm // 13,6W // 78lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS

DELTALIGHT

M26L - HALOSCAN HP SOFT 93014 MDL

23131 9010 B

For detailed installation instructions, please consult the manual : **23131_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 14


Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 14

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 14


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 7

Dimtype: non-dimmable

DELTALIGHT


M26L - HALOSCAN HP SOFT 93014 MDL

23131 9010 B



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 17


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 7

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 14


Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



23110 0040 HALOSCAN LINEAR SPREAD LENS




23110 0050 B HALOSCAN HONEYCOMB B


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m




23358 0020 SLM26L - PROFILE 2m

DELTALIGHT

M26L - HALOSCAN HP SOFT 93014 MDL


23131 9010 B




23358 0030 SLM26L - PROFILE 3m

SHIFTLINE M35R profile


Available Colours




23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m

Notes: