





SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

AVAILABLE IN
BLACK 20614 9300 B
WHITE 20614 9300 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.ADJUSTABLE LED POWER SUPPLY 500mA UP / DOWN - 3 settings: 1- 2800mA 2- 1860mA 3- 1300mA
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2800mA: LED cluster 123,7W / CRI>90 (R9: 68) / 3000K / 16507lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm) Or DOWN @ 1860mA: LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm) Or DOWN @ 1300mA: LED cluster 54,2W / CRI>90 (R9: 68) / 3000K / 8273lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
TM-30 VALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100 DOWN @ 1860mA: Rf: 89 / Rg: 97 UP @ 500mA: Rf: 92 / Rg: 100 DOWN @ 1300mA: Rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG1 RG0
LM80	L70 > 60000 L80 > 60000

DELTALIGHT

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

LED TECHNICS (LIGHT SOURCE)	DOWN @ 2800mA: 16507lm // 123,7W // 133lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W Or DOWN @ 1860mA: 11477lm // 79,4W // 144lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W Or DOWN @ 1300mA: 8273lm // 54,2W // 153lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2800mA: 12661lm // 142,3W // 89lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W Or DOWN @ 1860mA: 8803lm // 91,3W // 96lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W Or DOWN @ 1300mA: 6345lm // 62,3W // 102lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

Requirements

SUSPENSION SET 25 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT


Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90

For detailed installation instructions, please consult the manual : [20614_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

203 99 56 ANO CABLE BASE S ANO

☐

203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W






☐

DELTALIGHT

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B



Coversets

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐



DELTALIGHT

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

Suspension parts

	<u>274 97 10 B</u>	CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B	☐
	<u>274 97 10 W</u>	CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W	☐
	<u>328 25 43</u>	SUSPENSION SET 25 3m	☐
	<u>328 26 23 B</u>	CENTRAL SUSPENSION SUPERNOVA FLAT 3m B	☐
	<u>328 26 23 W</u>	CENTRAL SUSPENSION SUPERNOVA FLAT 3m W	☐

Electric connection parts

	<u>15225 0360 B</u>	CONNECTION ST B	☐
	<u>15225 0360 W</u>	CONNECTION ST W	☐

DELTALIGHT

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

Notes: