DELTALIGHT

SUPERNOVA FLAT 95 DOWN-UP 930

REFERENCE 20614 9300 B

AVAILABLE IN
BLACK 20614 9300 B
WHITE 20614 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.ADJUSTABLE LED POWER SUPPLY 500mA UP / DOWN - 3 settings: 1- 2800mA 2- 1860mA 3- 1300mA

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2800mA: LED cluster 123,7W / CRI>90 (R9: 68) / 3000K / 16507lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm) Or DOWN @ 1860mA: LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm) Or DOWN @ 1300mA: LED cluster 54,2W / CRI>90 (R9: 68) / 3000K / 8273lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
TM-30 VALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100 DOWN @ 1860mA: Rf: 89 / Rg: 97 UP @ 500mA: Rf: 92 / Rg: 100 DOWN @ 1300mA: Rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG1 RG0
LM80	L70 > 60000 L80 > 60000

DELTALIGHT

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

LED TECHNICS (LIGHT SOURCE)	DOWN @ 2800mA: 16507lm // 123,7W // 133lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W Or DOWN @ 1860mA: 11477lm // 79,4W // 144lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W Or DOWN @ 1300mA: 8273lm // 54,2W // 153lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2800mA: 12661lm // 142,3W // 89lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W Or DOWN @ 1860mA: 8803lm // 91,3W // 96lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W Or DOWN @ 1300mA: 6345lm // 62,3W // 102lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

Requirements

SUSPENSION SET 25 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90

For detailed installation instructions, please consult the manual : **20614_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐

203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B

204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W



204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B

204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO

204 80 80 B COVERSET S 80 B

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

204 80 80 W COVERSET S 80 W



204 90 90 ANO COVERSET S 90 ANO

204 90 90 B COVERSET S 90 B

204 90 90 W COVERSET S 90 W

Suspension parts



274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W



328 25 43 SUSPENSION SET 25 3m



328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

Electric connection parts

15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

SUPERNOVA FLAT 95 DOWN-UP 930

20614 9300 B

Notes: