



## INFORM SQ P392-6 DOWN 92767

25570 9220 B-B



AVAILABLE IN

**BLACK-BLACK** 25570 9220 B-B

**BLACK-FLEMISH GOLD** 25570 9220 B-FG

**WHITE-BLACK** 25570 9220 W-B

**WHITE-WHITE** 25570 9220 W-W



[View on website](#)



### General info

|                           |                                                                                                                                                      |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                               |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                    |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                 |
| <b>WEIGHT (KG)</b>        | 3.2                                                                                                                                                  |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                       |
| <b>INFORMATION</b>        | 72 x REFLECTOR FL-67°<br>EXCL.LED POWER SUPPLY 600/900mA-DC<br>INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m<br>INCL.1 x CABLE 2 x 0.75mm <sup>2</sup> |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, ENEC, EPD             |

### Lightsource info

|                                    |                                                                      |
|------------------------------------|----------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                  |
| <b>LIGHTSOURCE</b>                 | 2 x (LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 2700K / 1519-2196lm) |
| <b>TM-30 VALUES</b>                | Rf: 93 / Rg: 100                                                     |
| <b>SDCM</b>                        | SDCM3                                                                |
| <b>RISKGROUP</b>                   | RG1                                                                  |
| <b>LM80</b>                        | L80 > 60000                                                          |
| <b>BEAMANGLE</b>                   | 67°                                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 4392lm // 33,4W // 131lm/W                                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 3834lm // 38,4W // 100lm/W                                           |

### Requirements

INFORM POWER SUPPLY 45W  
INFORM SQ POWERBOX L 50W

### Options

CABLE BASE R / S  
COVERSET R 62-90-100 / S 62-80-90  
CONNECTION ST / CONNECTION TRIMLESS  
SUSPENSION ST / SUSPENSION TRIMLESS

# DELTALIGHT


## INFORM SQ P392-6 DOWN 92767

25570 9220 B-B

For detailed installation instructions, please consult the manual : [25570\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply



|                                                                                    |                                       |                          |
|------------------------------------------------------------------------------------|---------------------------------------|--------------------------|
|    | <b>203 99 55 ANO</b> CABLE BASE R ANO | <input type="checkbox"/> |
|                                                                                    | <b>203 99 55 B</b> CABLE BASE R B     | <input type="checkbox"/> |
|                                                                                    | <b>203 99 55 W</b> CABLE BASE R W     | <input type="checkbox"/> |
|  | <b>203 99 56 ANO</b> CABLE BASE S ANO | <input type="checkbox"/> |
|                                                                                    | <b>203 99 56 B</b> CABLE BASE S B     | <input type="checkbox"/> |
|                                                                                    | <b>203 99 56 W</b> CABLE BASE S W     | <input type="checkbox"/> |

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

|                                                                                    |                                                |                            |
|------------------------------------------------------------------------------------|------------------------------------------------|----------------------------|
|  | <b>25510 0385</b> INFORM POWER SUPPLY 45W DIMS | 1 <input type="checkbox"/> |
|                                                                                    | Dimtype: DALI                                  |                            |
|  | <b>25510 0430</b> INFORM POWER SUPPLY 45W      | 1 <input type="checkbox"/> |
|                                                                                    | Dimtype: non-dimmable                          |                            |

# DELTALIGHT

## INFORM SQ P392-6 DOWN 92767


25570 9220 B-B

### Power box

### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '!' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**25510 0480 B** INFORM SQ POWERBOX L 50W B

1

Dimtype: non-dimmable

**25510 0480 W** INFORM SQ POWERBOX L 50W W

1



**25510 0495 B** INFORM SQ POWERBOX L 50W DIM5 B


1

Dimtype: DALI

**25510 0495 W** INFORM SQ POWERBOX L 50W DIM5 W

1


### Coversets



**204 00 62 ANO** COVERSET R 62 ANO

**204 00 62 B** COVERSET R 62 B


**204 00 62 W** COVERSET R 62 W



**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B

**204 00 90 W** COVERSET R 90 W






**204 00 100 ANO** COVERSET R 100 ANO



# DELTALIGHT

## INFORM SQ P392-6 DOWN 92767

25570 9220 B-B

|                                                                                     |                      |                   |                          |
|-------------------------------------------------------------------------------------|----------------------|-------------------|--------------------------|
|                                                                                     | <u>204 00 100 B</u>  | COVERSET R 100 B  | <input type="checkbox"/> |
|                                                                                     | <u>204 00 100 W</u>  | COVERSET R 100 W  | <input type="checkbox"/> |
|    | <u>204 62 62 ANO</u> | COVERSET S 62 ANO | <input type="checkbox"/> |
|                                                                                     | <u>204 62 62 B</u>   | COVERSET S 62 B   | <input type="checkbox"/> |
|                                                                                     | <u>204 62 62 W</u>   | COVERSET S 62 W   | <input type="checkbox"/> |
|    | <u>204 80 80 ANO</u> | COVERSET S 80 ANO | <input type="checkbox"/> |
|                                                                                     | <u>204 80 80 B</u>   | COVERSET S 80 B   | <input type="checkbox"/> |
|                                                                                     | <u>204 80 80 W</u>   | COVERSET S 80 W   | <input type="checkbox"/> |
|  | <u>204 90 90 ANO</u> | COVERSET S 90 ANO | <input type="checkbox"/> |
|                                                                                     | <u>204 90 90 B</u>   | COVERSET S 90 B   | <input type="checkbox"/> |
|                                                                                     | <u>204 90 90 W</u>   | COVERSET S 90 W   | <input type="checkbox"/> |

### Suspension parts

|                                                                                     |                                           |                            |                          |
|-------------------------------------------------------------------------------------|-------------------------------------------|----------------------------|--------------------------|
|   | <u>328 10 01</u>                          | SUSPENSION TRIMLESS O.F.A. | <input type="checkbox"/> |
|                                                                                     | Cutout dimension (mm): 62 (CONCRETE: 102) |                            |                          |
|  | <u>15225 0340 B</u>                       | SUSPENSION ST B            | <input type="checkbox"/> |
|                                                                                     | Cutout dimension (mm): 27                 |                            |                          |


DELTA LIGHT

INFORM SQ P392-6 DOWN 92767

25570 9220 B-B

15225 0340 W SUSPENSION ST W

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: