





INFORM RI DOWN 92748

REFERENCE 26811 9220 W-B

AVAILABLE IN
NOIR-NOIR 26811 9220 B-B
NOIR-FLEMISH GOLD 26811 9220 B-FG
FLEMISH GOLD-NOIR 26811 9220 FG-B
BLANC-NOIR 26811 9220 W-B
BLANC-BLANC 26811 9220 W-W



 [View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Applique,Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non réglable
INFORMATION	96 x REFLECTOR WFL-71° EXCL LED POWER SUPPLY 700mA-DC
Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	C
CERTIFICATION	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm
SDMC	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	3456lm // 22,9W // 151lm/W
LED TECHNICS (LUMINAIRE)	2886lm // 26,3W // 110lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM (Remote)


Options

SUSPENSION SET 30 2x0,75 1,6m
 CABLE BASE R / S
 COVERSET R 62-90-100 / S 62-80-90

For detailed installation instructions, please consult the manual : [26811_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


le cable d'alimentation

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

les alimentations led

of Fixtures






les sets pour recouvrement plafond

	204 00 62 ANO COVERSET R 62 ANO	☐
---	--	--------------------------

DELTALIGHT

INFORM R1 DOWN 92748

26811 9220 W-B

	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐

DELTALIGHT

INFORM R1 DOWN 92748

26811 9220 W-B

<u>204 90 90 B</u>	COVERSET S 90 B	☐
<u>204 90 90 W</u>	COVERSET S 90 W	☐

les accessoires de suspension



<u>15225 0300 B</u>	SUSPENSION SET 30 2x0,75 1,6m B	☐
<u>15225 0300 W</u>	SUSPENSION SET 30 2x0,75 1,6m W	☐

les accessoires pour connexions électriques



<u>15225 0360 B</u>	CONNECTION ST B	☐
Cutout dimension (mm): 43		
<u>15225 0360 W</u>	CONNECTION ST W	☐

Notes: