



NOCTA SQ155 DOWN-UP 2VWFL 930 DIM5

30129 9305 A

AVAILABLE IN


ALU GREY 30129 9305 A

BLACK 30129 9305 B

FLEMISH BRONZE OUTDOOR 30129 9305 FBRX

ANTHRACITE 30129 9305 N

WHITE 30129 9305 W



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.2 x TUBE INCL.DIMMABLE LED POWER SUPPLY 700 mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm)
TM-30 VALUES	rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	960lm // 8W // 120lm/W
LED TECHNICS (LUMINAIRE)	285lm // 9,2W // 31lm/W

For detailed installation instructions, please consult the manual : [30129_XXX5_HAND.pdf](#)

DELTALIGHT

NOCTA SQ155 DOWN-UP 2VWFL 930 DIM5

30129 9305 A

Notes: