DELTALIGHT



FRAGMA M 93014 ADM DIM1P

REFERENCE 23611 931P W

AVAILABLE IN
BLACK 23611 931P B
WHITE 23611 931P W





View on website

General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	9 x LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 900mA-DC 3F MULTI ADAPTER

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	control button on luminaire
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 64) / 3000K / 2654lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	2654lm // 23,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	2123lm // 27W // 79lm/W

Requirements

TRACK 3F DIM

Options

FRAGMA 3X3 BEAM LENS

Accessories

FRAGMA 3X3 ACCESSORIES

FRAGMA M 93014 ADM DIM1P

23611 931P W

For detailed installation instructions, please consult the manual : **23611_XXXP_HAND.pdf**

DELTALIGHT

FRAGMA M 93014 ADM DIM1P

23611 931P W

FINISH YOUR SPECIFICATION

Light altering devices



23613 0020 FRAGMA M BEAM LENS 26°



23613 0050 FRAGMA M BEAM LENS 47°



23613 0080 FRAGMA M SOFTENING LENS



23613 0120 FRAGMA M LINEAR SPREAD LENS



23613 0170 FRAGMA M WALLWASH LENS



23613 0200 B FRAGMA M FLAPS B



23613 0230 B FRAGMA M HONEYCOMB B



23613 0260 B FRAGMA M RASTER B

DELTALIGHT

FRAGMA M 93014 ADM DIM1P

23611 931P W

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410 TRACK 3F DIM H 1m	1000 m	1.6 kg	
200 14 420 TRACK 3F DIM H 2m	2000 m	3.2 kg	
200 14 430 TRACK 3F DIM H 3m	3000 m	4.8 kg	

TRACK 3F DIM IN			Available Colours
200 13 410 TRACK 3F DIM IN 1m	1000 m	1.2 kg	
200 13 420 TRACK 3F DIM IN 2m	2000 m	2.4 kg	
200 13 430 TRACK 3F DIM IN 3m	3000 m	3.5 kg	

TRACK 3F DIM ON			Available Colours
200 12 410 TRACK 3F DIM ON 1m	1000 m	1.1 kg	
200 12 420 TRACK 3F DIM ON 2m	2000 m	2.1 kg	
200 12 430 TRACK 3F DIM ON 3m	3000 m	3.1 kg	

Notes: