




ENTERO RD-M TRIMLESS 93030

28430 9320 B

AVAILABLE IN
BLACK 28430 9320 B
FULL WHITE 28430 9320 FW
GOLD COLOURED 28430 9320 GC



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 18° & 45° available
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-25W / CRI>90 (R9: 52) / 3000K / 1524-2811lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	2811lm // 25W // 112lm/W
LED TECHNICS (LUMINAIRE)	2035lm // 28,8W // 71lm/W

Remarks
Max.500mA when using 1 accessory; max 450mA when using 2 accessories

Requirements
MOUNTING KIT ENTERO ROUND M
LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

Accessories
ENTERO M HONEYCOMB
ENTERO M LINEAR SPREAD LENS
ENTERO M SPREAD LENS
ENTERO M SOFTENING LENS
ENTERO M GLASS SBL

ENTERO RD-M TRIMLESS 93030

28430 9320 B


For detailed installation instructions, please consult the manual : [28430_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required
	 28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

☐

Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐

LED power supplies

of Fixtures













of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current









ENTERO RD-M TRIMLESS 93030

28430 9320 B

	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1	1	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 30		
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	1	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 30		
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
	Dimtype: WDL = wireless dimmable		
	Cutout dimension (mm): 45		
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	1	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 30		
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	1	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 30		
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	1	☐
	Dimtype: WDL = wireless dimmable		
	Cutout dimension (mm): 45		
	300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1	1	☐
	Dimtype: 1-10V		
	Cutout dimension (mm): 30		
	300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		











ENTERO RD-M TRIMLESS 93030

28430 9320 B

	300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL Dimtype: non-dimmable Cutout dimension (mm): 30	1	☐
	300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 45	1	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: mains (phase cut-off) or push button Cutout dimension (mm): 56	1 1 1	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	2(2) 2(2) 2(1)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1(1) 1(0) 1(0)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	1 - 1	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1(1) 1(0) 1(0)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	3(3) 3(2) 2(1)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	1(1) 1(0) 0	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1) 1(0) 0	☐

ENTERO RD-M TRIMLESS 93030






28430 9320 B

	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	2->2 2 2	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1 1 1	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1 1 1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 1 1	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	2(2) 2(2) 2(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	1 1 1	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	1 1	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	1 1 0	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	1(1)	☐


DELTALIGHT

ENTERO RD-M TRIMLESS 93030


28430 9320 B

	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68	1(0)	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 60			
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1(0)	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 60			
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 30			
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 30			
	21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 30			

Mounting kits

	28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.	☐
Cutout dimension (mm): 127		

Mounting kits stretched ceiling







	28400 0080 MOUNTING KIT ENTERO RD-M CSC	☐
	28400 0140 MOUNTING KIT ENTERO RD-M WSC	☐

DELTALIGHT

ENTERO RD-M TRIMLESS 93030

28430 9320 B

Light altering devices

	28500 0070 ENTERO M LINEAR SPREAD LENS	☐
	28500 0080 ENTERO M SPREAD LENS	☐
	28500 0090 ENTERO M SOFTENING LENS	☐
	28500 0100 ENTERO M GLASS SBL	☐
	28500 0110 B ENTERO M HONEYCOMB SINGLE USE B	☐
	28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B	☐

Replaceable reflector / lens

	24611 0220 SPY 66 REFLECTOR 18°	☐
	24611 0230 SPY 66 REFLECTOR 30°	☐

DELTALIGHT

ENTERO RD-M TRIMLESS 93030

28430 9320 B



24611 0240 SPY 66 REFLECTOR 45°



Notes: