
DELTALIGHT




# M20/M26H - OBIN 92724 MDL

**REFERENCE** 30513 9220 CR

AVAILABLE IN
**BLACK** 30513 9220 B
**BRUSHED ALU** 30513 9220 BRA
**BRUSHED ANTHRACITE** 30513 9220 BRAT
**BRUSHED BROWN BRONZE** 30513 9220 BRBB
**BRUSHED GOLD** 30513 9220 BRG
**BRUSHED OLD BRONZE** 30513 9220 BROB
**CREAM** 30513 9220 CR
**WHITE** 30513 9220 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 45° swiveling, 360° rotatable |
| **INFORMATION** | LENS FL-24°<br>EXCL.LED POWER SUPPLY 48V-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 24° |
| **LED TECHNICS (LIGHT SOURCE)** | 1458lm // 11,6W // 125lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1217lm // 13W // 91lm/W |

## Requirements

SPY 90 TUBE
LED POWER SUPPLY 48V-DC

## Options

DIMMABLE MODULATOR

## Accessories

HONEYCOMB 75

DELTALIGHT

# M20/M26H - OBIN 92724 MDL

30513 9220 CR

For detailed installation instructions, please consult the manual : **30513_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**21032 0030** SMART 48 MODULATOR PLUG-IN WD — 14


**Dimtype: WDL = wireless dimmable**

### SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 14

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 14


**Dimtype: WDL = wireless dimmable**

### LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 7

**Dimtype: non-dimmable**


# M20/M26H - OBIN 92724 MDL

30513 9220 CR




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 14


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 7

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 14

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

## Light altering devices





**19810 0110 B** HONEYCOMB 75 SINGLE USE B




# M20/M26H - OBIN 92724 MDL

30513 9220 CR

## Finish your product

| | | |
|---|---|---|
|  | **19810 0170 B** | SPY 90 TUBE B |
| | **19810 0170 CR** | SPY 90 TUBE CR |
| | **19810 0170 DC** | SPY 90 TUBE DC |
| | **19810 0170 FBR** | SPY 90 TUBE FBR |
| | **19810 0170 FG** | SPY 90 TUBE FG |
| | **19810 0170 GC** | SPY 90 TUBE GC |
| | **19810 0170 PB** | SPY 90 TUBE PB |
| | **19810 0170 W** | SPY 90 TUBE W |


## COMPATIBLE COMPOSABLES

| SHIFTLINE M26H profile | | Available Colours |
|---|---|---|
|  | **23359 0000** SLM26H - PROFILE | |
|  | **23359 0010** SLM26H - PROFILE 1m | |
|  | **23359 0020** SLM26H - PROFILE 2m | |

DELTALIGHT

# M20/M26H - OBIN 92724 MDL

30513 9220 CR




**23359 0030** SLM26H - PROFILE 3m



## SPLITLINE M20 ST profile — Available Colours




**23397 0000** SPM20 ST - PROFILE






**23397 0020** SPM20 ST - PROFILE 2m







**23397 0030** SPM20 ST - PROFILE 3m




## SPLITLINE M20 profile — Available Colours





**420 20 10 00** SPM20 - PROFILE 1m







**420 20 20 00** SPM20 - PROFILE 2m






**420 20 30 00** SPM20 - PROFILE 3m






**23301 0000** SPM20 - PROFILE B



Notes: