



M20/M26H - OBIN 92724 MDL

30513 9220 CR

AVAILABLE IN

BLACK 30513 9220 B

BRUSHED ALU 30513 9220 BRA

BRUSHED ANTHRACITE 30513 9220 BRAT



BRUSHED BROWN BRONZE 30513 9220 BRBB

BRUSHED GOLD 30513 9220 BRG

BRUSHED OLD BRONZE 30513 9220 BROB

CREAM 30513 9220 CR

WHITE 30513 9220 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-24° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	24°
LED TECHNICS (LIGHT SOURCE)	1458lm // 11,6W // 125lm/W
LED TECHNICS (LUMINAIRE)	1217lm // 13,3W // 91lm/W

Requirements

SPY 90 TUBE

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

HONEYCOMB 75

For detailed installation instructions, please consult the manual : [30513_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

14


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

14

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

14


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN


7

Dimtype: non-dimmable

DELTALIGHT

M20/M26H - OBIN 92724 MDL

30513 9220 CR




63 114 125

300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

14 ☐

Dimtype: non-dimmable




17 298 30

21012 0230 LED POWER SUPPLY 48V-DC / 100W

7 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40



22 392 30


21012 0240 LED POWER SUPPLY 48V-DC / 200W

14 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



13 075

19810 0110 B HONEYCOMB 75 SINGLE USE B

☐

DELTALIGHT




M20/M26H - OBIN 92724 MDL

30513 9220 CR

Finish your product

	19810 0170 B	SPY 90 TUBE B	☐
	19810 0170 CR	SPY 90 TUBE CR	☐
	19810 0170 DC	SPY 90 TUBE DC	☐
	19810 0170 FBR	SPY 90 TUBE FBR	☐
	19810 0170 FG	SPY 90 TUBE FG	☐
	19810 0170 GC	SPY 90 TUBE GC	☐
	19810 0170 PB	SPY 90 TUBE PB	☐
	19810 0170 W	SPY 90 TUBE W	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile	Available Colours
	23359 0000 SLM26H - PROFILE 
	23359 0010 SLM26H - PROFILE 1m 
	23359 0020 SLM26H - PROFILE 2m 

DELTALIGHT

M20/M26H - OBIN 92724 MDL

30513 9220 CR



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: