




FRAX M SUPERSPOT 93008

26111 9310 N

AVAILABLE IN
ALU GREY 26111 9310 A
FLEMISH BRONZE OUTDOOR 26111 9310 FBRX
ANTHRACITE 26111 9310 N



 [View on website](#)




General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.4
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	7 x LENS SP-8° INCL.LED POWER SUPPLY 900mA-DC
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 18,2W / CRI>90 (R9: 60) / 3000K / 2064lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	8°
LED TECHNICS (LIGHT SOURCE)	2064lm // 18,2W // 113lm/W
LED TECHNICS (LUMINAIRE)	1775lm // 20,9W // 85lm/W
Options	
FRAX ANTI VANDAL SCREWS	
Accessories	
FRAX M KAP	

For detailed installation instructions, please consult the manual : [26111_XX10_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices



26070 0020 N FRAX M KAP N

☐

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

Notes: