



NOCTA SQ155 VWFL 930

30123 9300 B

AVAILABLE IN


ALU GREY 30123 9300 A

BLACK 30123 9300 B

FLEMISH BRONZE OUTDOOR 30123 9300 FBRX

ANTHRACITE 30123 9300 N

WHITE 30123 9300 W



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LENS INCL.LED POWER SUPPLY 350 mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 734lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	734lm // 5,8W // 127lm/W
LED TECHNICS (LUMINAIRE)	448lm // 6,7W // 67lm/W

For detailed installation instructions, please consult the manual : [30123_XXX0_HAND.pdf](#)

DELTALIGHT

NOCTA SQ155 VWFL 930

30123 9300 B

Notes: