



## OML50 - INFORM DU HO 2624mm 8+16+8LED 93063

31437 9330 B

BESCHIKBAAR IN  
**ZWART** 31437 9330 B



[Bekijk op website](#)



### Algemene info

|                               |  |
|-------------------------------|--|
| <b>LOCATIE</b>                | binnen   |
| <b>STOF EN WATERDICHTHEID</b> | IP20   |
| <b>GEWICHT (KG)</b>           | 2.4  |
| <b>INFO</b>                   | CLUSTER DOWN: 2663lm/m<br>CLUSTER UP: 2663lm/m<br>INCL.LED POWER SUPPLY<br>CABLING 1 CIRCUIT |

### Elektrische info

|                        |                      |
|------------------------|----------------------|
| <b>INGANGSSPANNING</b> | 220-240V / 0 50-60Hz |
| <b>KLASSE</b>          | I                    |
| <b>VOEDING</b>         | YES                  |
| <b>DIM TYPE</b>        | niet dimbaar         |
| <b>ENERGIE KLASSE</b>  | E                    |
| <b>CERTIFICATEN</b>    | EPD, RCM             |

### Info lichtbron

|                                 |  |
|---------------------------------|--|
| <b>LIGHTSOURCE NAME</b>         | LED  |
| <b>LICHTBRON</b>                | DOWN: LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm<br>UP: LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm |
| <b>TM-30-15 WAARDEN</b>         | Rf: 92 / Rg: 100   |
| <b>SDCM</b>                     | SDCM3  |
| <b>RISK-GROEP</b>               | RG1  |
| <b>LM80</b>                     | L80 > 60000  |
| <b>BEAMANGLE</b>                | 63°  |
| <b>LED TECHNIEK (LICHTBRON)</b> | DOWN: 6989lm // 48,4W // 145lm/W<br>UP: 6989lm // 48,4W // 145lm/W   |

Notes: