





M20/M26H - JUM-OH! 2R 92730 MDL

29415 9220 B

AVAILABLE IN
BLACK 29415 9220 B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 4W / CRI>90 (R9: 55) / 2700K / 439lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	439lm // 4W // 110lm/W
LED TECHNICS (LUMINAIRE)	363lm // 4,6W // 79lm/W

Requirements	
LED POWER SUPPLY 48V-DC	

Options	
DIMMABLE MODULATOR	

For detailed installation instructions, please consult the manual : [29415_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

41

Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

41

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

41

Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

21

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN


52

Dimtype: non-dimmable





DELTALIGHT

M20/M26H - JUM-OH! 2R 92730 MDL

29415 9220 B

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	21	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	43	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		





COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile		Available Colours
	<u>23359 0000</u> SLM26H - PROFILE	 
	<u>23359 0010</u> SLM26H - PROFILE 1m	 
	<u>23359 0020</u> SLM26H - PROFILE 2m	         
	<u>23359 0030</u> SLM26H - PROFILE 3m	         
SPLITLINE M20 ST profile		Available Colours
	<u>23397 0000</u> SPM20 ST - PROFILE	 
	<u>23397 0020</u> SPM20 ST - PROFILE 2m	 
	<u>23397 0030</u> SPM20 ST - PROFILE 3m	 

DELTALIGHT

M20/M26H - JUM-OH! 2R 92730 MDL

29415 9220 B

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: