

## LOGIC LINEAR ON 440 94025 DIM5

30827 9425 W

AVAILABLE IN



**ALU GREY** 30827 9425 A

**BLACK** 30827 9425 B

**FLEMISH BRONZE OUTDOOR** 30827 9425 FBRX

**ANTHRACITE** 30827 9425 N

**WHITE** 30827 9425 W



[View on website](#)



### General info

|                                             |                                                                     |
|---------------------------------------------|---------------------------------------------------------------------|
| <b>LOCATION</b>                             | outdoor                                                             |
| <b>INSTALLATION</b>                         | Floor Surface mounted, Wall Surface mounted                         |
| <b>INGRESS PROTECTION</b>                   | IP67                                                                |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK07                                                                |
| <b>WEIGHT (KG)</b>                          | 1                                                                   |
| <b>INFORMATION</b>                          | 8 x LENS FL-25°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | E        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 14,4W / CRI>90 (R9: 64) / 4000K / 1949lm |
| <b>TM-30 VALUES</b>                | Rf: 91 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>RISKGROUP</b>                   | RG2                                                  |
| <b>LM80</b>                        | L80 > 150000                                         |
| <b>BEAMANGLE</b>                   | 25°                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1949lm // 14,4W // 131lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 1613lm // 16,6W // 97lm/W                            |

### Requirements

WALL BRACKET SET  
FLOOR BRACKET SET  
IP68 CABLE + CONNECTOR 5P  
LED POWER SUPPLY 48V-DC

### Options

THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30827\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                      | # of Fixtures             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |                                                                                                                                                                                      | Min current   Max current |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>171</div><div>38</div><div>63</div></div></div>                                                                                                                                                                                                                 | <div><div><div><div><b>21032 0390</b></div><div>LED POWER SUPPLY 48V-DC / 90W</div></div><div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 75</div></div></div></div> | 5 <div></div>             |
| Fixation components                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                      |                           |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>35</div><div>31</div><div>67</div></div></div>                                                                                                                                                                                                                  | <div><div><div><div><b>30810 0040</b></div><div>LOGIC LINEAR 880 BOX EXTEND</div></div></div></div>                                                                                  | <div></div>               |
|                                                                                                                                                                                                                                                                                                                                                             | <div><div><div><div><b>30810 0040 INOX</b></div><div>WALL BRACKET SET 60 INOX</div></div></div></div>                                                                                | <div></div>               |
|                                                                                                                                                                                                                                                                                                                                                             | <div><div><div><div><b>30810 0040 N</b></div><div>WALL BRACKET SET 60 N</div></div></div></div>                                                                                      | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>28</div><div>42</div><div>100</div></div></div>                                                                                                                                                                                                                 | <div><div><div><div><b>30810 0050 INOX</b></div><div>WALL BRACKET SET 100 INOX</div></div></div></div>                                                                               | <div></div>               |
|                                                                                                                                                                                                                                                                                                                                                             | <div><div><div><div><b>30810 0050 N</b></div><div>WALL BRACKET SET 100 N</div></div></div></div>                                                                                     | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>28</div><div>42</div><div>200</div></div></div>                                                                                                                                                                                                                 | <div><div><div><div><b>30810 0060 INOX</b></div><div>WALL BRACKET SET 200 INOX</div></div></div></div>                                                                               | <div></div>               |
|                                                                                                                                                                                                                                                                                                                                                             | <div><div><div><div><b>30810 0060 N</b></div><div>WALL BRACKET SET 200 N</div></div></div></div>                                                                                     | <div></div>               |

# DELTALIGHT

## LOGIC LINEAR ON 440 94025 DIM5

30827 9425 W



**30810 0070 INOX** FLOOR BRACKET SET INOX

☐

### Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m

☐

**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m

☐

**30810 0100** THROUGH WIRING SET IP68 440

☐

Notes: