



DEEP RINGO HE 92720

19440 9220 FBR

AVAILABLE IN

NOIR 19440 9220 B

ALU BROSSÉ 19440 9220 BRA

ANTHRACITE BROSSÉ 19440 9220 BRAT

BRONZE BRUN BROSSÉ 19440 9220 BRBB

CUIVRE BROSSÉ 19440 9220 BRCU

OR BROSSÉ 19440 9220 BRG

BRONZE VIEUX BROSSÉ 19440 9220 BROB

CRÈME 19440 9220 CR

FLEMISH BRONZE 19440 9220 FBR

FLEMISH GOLD 19440 9220 FG

COULEUR OR 19440 9220 GC

NOIR PIANO 19440 9220 PB

BLANC 19440 9220 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP43/20
WEIGHT (KG)	0.2
ADJUSTABILITY	non réglable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	EPD, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm
RVALUES	rf: 96 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	905lm // 6W // 150lm/W
LED TECHNICS (LUMINAIRE)	774lm // 6,9W // 112lm/W

Remarks

High Efficacy : > 100lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : [19440_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

les batteries de secours







	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	Cutout dimension (mm): 27	
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

DEEP RINGO HE 92720

19440 9220 FBR

les alimentations led

of Fixtures

web2print_power_supply_info_box			Min current Max current
	300 90 91 LED POWER SUPPLY 350mA-DC / 15W Dimtype: non dimmable Cutout dimension (mm): 40	2(1)	☐
	300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 Dimtype: fin de phase Cutout dimension (mm): 42	1	☐
	300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	2->2	☐
	21012 0515 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1)	☐
	21012 0520 LED POWER SUPPLY 350mA-DC / 8W Dimtype: non dimmable Cutout dimension (mm): 47	1(0)	☐
	21012 0575 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 55	2->3(2)	☐

Notes: