DELTALIGHT



M20/M26H - OBIN 93024 MDL

REFERENCE 30513 9320 CR

AVAILABLE IN
BLACK 30513 9320 B
BRUSHED ALU 30513 9320 BRA
BRUSHED ANTHRACITE 30513 9320 BRAT
BRUSHED BROWN BRONZE 30513 9320 BRBB
BRUSHED GOLD 30513 9320 BRG
BRUSHED OLD BRONZE 30513 9320 BROB
CREAM 30513 9320 CR
WHITE 30513 9320 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-24° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	24°
LED TECHNICS (LIGHT SOURCE)	1524lm // 11,6W // 131lm/W
LED TECHNICS (LUMINAIRE)	1272lm // 13W // 95lm/W

Requirements

SPY 90 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

HONEYCOMB 75

DELTALIGHT

M20/M26H - OBIN 93024 MDL

30513 9320 CR

For detailed installation instructions, please consult the manual : **30513_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 14 ☐

Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 14 ☐

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 14 ☐

Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 7 ☐

Dimtype: non-dimmable

M20/M26H - OBIN 93024 MDL

30513 9320 CR



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 14

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 7

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 14

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



19810 0110 B HONEYCOMB 75 SINGLE USE B

M20/M26H - OBIN 93024 MDL

30513 9320 CR

Finish your product

	**19810 0170 B** SPY 90 TUBE B	☐
	19810 0170 CR SPY 90 TUBE CR	☐
	19810 0170 DC SPY 90 TUBE DC	☐
	19810 0170 FBR SPY 90 TUBE FBR	☐
	19810 0170 FG SPY 90 TUBE FG	☐
	19810 0170 GC SPY 90 TUBE GC	☐
	19810 0170 PB SPY 90 TUBE PB	☐
	19810 0170 W SPY 90 TUBE W	☐

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile	Available Colours
 **23359 0000** SLM26H - PROFILE	
 **23359 0010** SLM26H - PROFILE 1m	
 **23359 0020** SLM26H - PROFILE 2m	

DELTALIGHT

M20/M26H - OBIN 93024 MDL

30513 9320 CR



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE





23397 0020 SPM20 ST - PROFILE 2m





23397 0030 SPM20 ST - PROFILE 3m



SPLITLINE M20 profile — Available Colours



420 20 10 00 SPM20 - PROFILE 1m





420 20 20 00 SPM20 - PROFILE 2m





420 20 30 00 SPM20 - PROFILE 3m





23301 0000 SPM20 - PROFILE B



Notes: