



SOLI - FORM 110 92767 DIM5

27132 9225 B-B



AVAILABLE IN

BLACK-BLACK 27132 9225 B-B

BLACK-FLEMISH GOLD 27132 9225 B-FG

WHITE-BLACK 27132 9225 W-B

WHITE-WHITE 27132 9225 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,3W / CRI>90 (R9: 50) / 2700K / 2928lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2928lm // 22,3W // 131lm/W
LED TECHNICS (LUMINAIRE)	2556lm // 25,6W // 100lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27132_XXX5_HAND.pdf](#)

SOLI - FORM 110 92767 DIM5

27132 9225 B-B

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable		4
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable		9
1729830 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40		4
2239230 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40		8

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
2319 27111 0020 SOLI - PROFILE 2m	
2319 27111 0030 SOLI - PROFILE 3m	

Notes:

DELTALIGHT

SOLI - FORM 110 92767 DIM5

27132 9225 B-B