
DELTALIGHT




SPY 52 93020 ADM DIM5

REFERENCE 19834 9325 W

AVAILABLE IN
BLACK 19834 9325 B
FULL WHITE 19834 9325 FW
WHITE 19834 9325 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° 3F MULTI DIMMABLE POWER ADAPTER 700mA Optional REFLECTORS 30° & 45° available

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1467lm // 12,4W // 118lm/W
LED TECHNICS (LUMINAIRE)	919lm // 14,3W // 64lm/W

Requirements

SPY 52 TUBE
TRACK 3F DIM

For detailed installation instructions, please consult the manual : **19834_XXX5_HAND.pdf**


DELTALIGHT

SPY 52 93020 ADM DIM5


19834 9325 W

FINISH YOUR SPECIFICATION


Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B ☐




19810 0020 LINEAR SPREAD LENS 42 ☐




19810 0030 SPREAD LENS 42 ☐



19810 0040 SOFTENING LENS 42 ☐




19810 0050 GLASS SBL 42 ☐



19810 0060 B HONEYCOMB 42 DOUBLE USE B ☐

Finish your product



19810 0100 B SPY 52 TUBE B ☐

19810 0100 FBR SPY 52 TUBE FBR ☐



19810 0100 FG SPY 52 TUBE FG ☐

SPY 52 93020 ADM DIM5

19834 9325 W

19810 0100 GC	SPY 52 TUBE GC	☐
19810 0100 W	SPY 52 TUBE W	☐

Replaceable reflector / lens

	**19810 0180** SPY 52 REFLECTOR 20°	☐
	**19810 0190** SPY 52 REFLECTOR 45°	☐
	**19810 0240** SPY 52 REFLECTOR 30°	☐

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410 TRACK 3F DIM H 1m	1000 m	1.6 kg	● ○
200 14 420 TRACK 3F DIM H 2m	2000 m	3.2 kg	● ○
200 14 430 TRACK 3F DIM H 3m	3000 m	4.8 kg	● ○

TRACK 3F DIM IN			Available Colours
200 13 410 TRACK 3F DIM IN 1m	1000 m	1.2 kg	● ○
200 13 420 TRACK 3F DIM IN 2m	2000 m	2.4 kg	● ○
200 13 430 TRACK 3F DIM IN 3m	3000 m	3.5 kg	● ○

TRACK 3F DIM ON			Available Colours
200 12 410 TRACK 3F DIM ON 1m	1000 m	1.1 kg	● ● ○
200 12 420 TRACK 3F DIM ON 2m	2000 m	2.1 kg	● ● ○
200 12 430 TRACK 3F DIM ON 3m	3000 m	3.1 kg	● ● ○

SPY 52 93020 ADM DIM5

19834 9325 W

Notes: