



COMPO S WALLWASH S HP 940

9 15723 9400 C


AVAILABLE IN
CHROME 9 15723 9400 C
BLANC 9 15723 9400 W



EXCLUSIVELY AVAILABLE IN INDIA



0-30°/355°



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.166
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9,3W / CRI>90 / 4000K / 973lm
SDMC	SDCM2
RISKGROUP	RG1
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	973lm // 9,3W // 104lm/W
LED TECHNICS (LUMINAIRE)	432lm // 10,7W // 40lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

For detailed installation instructions, please consult the manual : [9_15723_XXX0_HAND.pdf](#)

COMPO S WALLWASH S HP 940

9 15723 9400 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
15710 3400	LED POWER SUPPLY MULTIPOWER 25W NO DIM 500mA	1->2 ☐
15710 3900	LED POWER SUPPLY MULTIPOWER 10W DIM8 500mA	1 ☐
15710 4600	LED POWER SUPPLY MULTIPOWER 12W DIM1 500mA	1 ☐
15710 5400	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1->2 ☐
Dimtype: DALI		

kit de montage	
	15710 0010 B MOUNTING KIT COMPO S TRIM B ☐
Cutout dimension (mm): 55	
	15710 0010 W MOUNTING KIT COMPO S TRIM W ☐
	15710 0040 MOUNTING KIT COMPO S TRIMLESS ☐
Cutout dimension (mm): 55	

DELTALIGHT

COMPO S WALLWASH S HP 940

9 15723 9400 C

Notes: