



OML50 CT - 48V 100W 1,5m + PRISMATIC LENS D TW 1640mm 950 DIM5

31164 9005 B

BESCHIKBAAR IN
ZWART 31164 9005 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.7
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@ 2700K: LED cluster 30W / CRI>90 (R9: 50) / 2700K-5000K / 4011lm Or @ 5000K: LED cluster 27,4W / CRI>90 (R9: 50) / 2700K-5000K / 4781lm
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	@ 2700K: 4011lm // 30W // 134lm/W Or @ 5000K: 4781lm // 27,4W // 174lm/W

Opties

WIRELESS CONTROL DIM5

Notes: