





SPY 90 TW 96545 ADM DIM5

19884 9035 W

AVAILABLE IN
BLACK 19884 9035 B
WHITE 19884 9035 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° 3F DIMMABLE POWER ADAPTER 500mA-DC - (DALI DT8) Optional REFLECTORS 18° & 30° available

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1453lm // 20,5W // 71lm/W

Requirements

SPY 90 TUBE
TRACK 3F DIM

Accessories

HONEYCOMB 75
SPREAD LENS 75
LINEAR SPREAD LENS 75
SOFTENING LENS 75
GLASS SBL 75

DELTALIGHT


SPY 90 TW 96545 ADM DIM5

19884 9035 W

For detailed installation instructions, please consult the manual : [19884_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices




¹³ **19810 0110 B** HONEYCOMB 75 SINGLE USE B

☐




¹⁴ **19810 0120 B** HONEYCOMB 75 DOUBLE USE B

☐




¹³ **19810 0130** GLASS SBL 75

☐



¹³ **19810 0140** LINEAR SPREAD LENS 75

☐



¹³ **19810 0150** SOFTENING LENS 75

☐



¹³ **19810 0160** SPREAD LENS 75

☐

Finish your product



²⁸ **19810 0170 B** SPY 90 TUBE B

☐

DELTALIGHT

SPY 90 TW 96545 ADM DIM5

19884 9035 W

19810 0170 CR	SPY 90 TUBE CR	☐
19810 0170 DC	SPY 90 TUBE DC	☐
19810 0170 FBR	SPY 90 TUBE FBR	☐
19810 0170 FG	SPY 90 TUBE FG	☐
19810 0170 GC	SPY 90 TUBE GC	☐
19810 0170 PB	SPY 90 TUBE PB	☐
19810 0170 W	SPY 90 TUBE W	☐

Replaceable reflector / lens

	19810 0200 SPY 90 REFLECTOR 18°	☐
	19810 0210 SPY 90 REFLECTOR 30°	☐
	19810 0220 SPY 90 REFLECTOR 45°	☐

COMPATIBLE TRACKS

TRACK 3F DIM H				Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m	1.6 kg	☒ ☐
200 14 420	TRACK 3F DIM H 2m	2000 m	3.2 kg	☒ ☐
200 14 430	TRACK 3F DIM H 3m	3000 m	4.8 kg	☒ ☐
TRACK 3F DIM IN				Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m	1.2 kg	☒ ☐

DELTALIGHT

SPY 90 TW 96545 ADM DIM5

19884 9035 W

200 13 420 TRACK 3F DIM IN 2m	2000 m	2.4 kg	 
200 13 430 TRACK 3F DIM IN 3m	3000 m	3.5 kg	 
TRACK 3F DIM ON		Available Colours	
200 12 410 TRACK 3F DIM ON 1m	1000 m	1.1 kg	  
200 12 420 TRACK 3F DIM ON 2m	2000 m	2.1 kg	  
200 12 430 TRACK 3F DIM ON 3m	3000 m	3.1 kg	  

Notes: