
DELTALIGHT




M20/M26H - SPY 39 FRAMER 927 MDL

REFERENCE 23417 9200 B

AVAILABLE IN
BLACK 23417 9200 B





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 974lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	332lm // 9,9W // 34lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : **23417_XXX0_HAND.pdf**

DELTALIGHT

M20/M26H - SPY 39 FRAMER 927 MDL

23417 9200 B


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 19


Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 19


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24

Dimtype: non-dimmable

M20/M26H - SPY 39 FRAMER 927 MDL


23417 9200 B



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20

Dimtype: non-dimmable


Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES


SHIFTLINE M26H profile — Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m







23397 0030 SPM20 ST - PROFILE 3m

DELTALIGHT

M20/M26H - SPY 39 FRAMER 927 MDL

23417 9200 B

SPLITLINE M20 profile	Available Colours
 **420 20 10 00** SPM20 - PROFILE 1m	
 **420 20 20 00** SPM20 - PROFILE 2m	
 **420 20 30 00** SPM20 - PROFILE 3m	
 **23301 0000** SPM20 - PROFILE B	

Notes: