




M20/M26H - SPY 39 FRAMER 927
MDL

23417 9200 B

AVAILABLE IN
BLACK 23417 9200 B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 974lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	332lm // 9,9W // 34lm/W

Requirements	
LED POWER SUPPLY 48V-DC	

Options	
DIMMABLE MODULATOR	

For detailed installation instructions, please consult the manual : [23417_XXX0_HAND.pdf](#)

M20/M26H - SPY 39 FRAMER 927 MDL

23417 9200 B

FINISH YOUR SPECIFICATION


Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

19

Dimtype: WDL = wireless dimmable


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

19

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN



24

Dimtype: non-dimmable




DELTALIGHT

M20/M26H - SPY 39 FRAMER 927 MDL

23417 9200 B

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	10	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	20	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		





COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile	Available Colours
 23359 0000 SLM26H - PROFILE	 
 23359 0010 SLM26H - PROFILE 1m	 
 23359 0020 SLM26H - PROFILE 2m	         
 23359 0030 SLM26H - PROFILE 3m	         
SPLITLINE M20 ST profile	Available Colours
 23397 0000 SPM20 ST - PROFILE	 
 23397 0020 SPM20 ST - PROFILE 2m	 
 23397 0030 SPM20 ST - PROFILE 3m	 

DELTALIGHT

M20/M26H - SPY 39 FRAMER 927 MDL

23417 9200 B

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: