
DELTALIGHT




DOT.COM S3 ST 92759

REFERENCE 424 211 03 923 W-B

AVAILABLE IN
BLACK-BLACK 424 211 03 923 B-B
WHITE-BLACK 424 211 03 923 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 58 x 20
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	min.8
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	3 x REFLECTOR WFL-56° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 3,1W / CRI>90 (R9: 50) / 2700K / 333lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	59°
LED TECHNICS (LIGHT SOURCE)	333lm // 3,1W // 109lm/W
LED TECHNICS (LUMINAIRE)	216lm // 4W // 61lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : **424_211_03_XXX_HAND.pdf**

DOT.COM S3 ST 92759

424 211 03 923 W-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 4

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 4

Dimtype: DALI

Cutout dimension (mm): 45

DOT.COM S3 ST 92759


424 211 03 923 W-B



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 4

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 4

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 5

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 8(8)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 2->6(4)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 5


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 5(4)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 3->12(12)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 2->5(4)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 2->5(4)


Dimtype: DALI

Cutout dimension (mm): 55

DELTALIGHT

DOT.COM S3 ST 92759


424 211 03 923 W-B



300 90 135 LED POWER SUPPLY MULTI-POWER HV 5->9

Dimtype: non-dimmable


Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 2->5

Dimtype: non-dimmable


Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 2->6

Dimtype: 1-10V


Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 2->6

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 8(8)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 2->6

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 2->3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 3->4

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 5

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 2->2


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 40

DELTALIGHT

DOT.COM S3 ST 92759

424 211 03 923 W-B



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 4

Dimtype: DALI

Cutout dimension (mm): 30

Notes: