DELTALIGHT



OML50 CT - 48V 100W 1,5m + PRISMATIC LENS D TW 1968mm 950 DIM5

REFERENCE 31165 9005 B

AVAILABLE IN
BLACK 31165 9005 B

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.1
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 36W / CRI>90 (R9: 50) / 2700K-5000K / 4813lm Or @ 5000K: LED cluster 32,9W / CRI>90 (R9: 50) / 2700K-5000K / 5737lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 4813lm // 36W // 134lm/W Or @ 5000K: 5737lm // 32,9W // 174lm/W

Options

WIRELESS CONTROL DIM5

Notes: