
DELTALIGHT




M20/M26H - SPY 272 92730 DIM5

REFERENCE 23314 9225 B

AVAILABLE IN
BLACK 23314 9225 B
WHITE 23314 9225 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	919lm // 13,3W // 69lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

Accessories

VISOR 27

For detailed installation instructions, please consult the manual : **23314_XXX5_HAND.pdf**

M20/M26H - SPY 272 92730 DIM5

23314 9225 B


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 7 ☐

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 18 ☐


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 7 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 15 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



24144 0040 B VISOR 27 B ☐

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL

Available Colours



30411 9205 SHIFTLINE M26H + SBL 2m DIM5


DELTALIGHT

M20/M26H - SPY 272 92730 DIM5


23314 9225 B




30411 9305 SHIFTLINE M26H + SBL 2m DIM5




30412 9205 SHIFTLINE M26H + SBL 3m DIM5



30412 9305 SHIFTLINE M26H + SBL 3m DIM5




30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m







23359 0030 SLM26H - PROFILE 3m

DELTALIGHT

M20/M26H - SPY 272 92730 DIM5

23314 9225 B

SPLITLINE M20 ST profile		Available Colours
	**23397 0000** SPM20 ST - PROFILE	
	**23397 0020** SPM20 ST - PROFILE 2m	
	**23397 0030** SPM20 ST - PROFILE 3m	

SPLITLINE M20 profile		Available Colours
	**420 20 10 00** SPM20 - PROFILE 1m	
	**420 20 20 00** SPM20 - PROFILE 2m	
	**420 20 30 00** SPM20 - PROFILE 3m	
	**23301 0000** SPM20 - PROFILE B	

Notes: