




SOLI - SHHH PLUS 120/4 LILAC
DIM5

21423 0005 B

AVAILABLE IN
BLACK 21423 0005 B
WHITE 21423 0005 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.3
ADJUSTABILITY	non adjustable
INFORMATION	FOR max.4 x SOLI 52 - SHHH or max.3 x SOLI - 52 SHHH SOFT INCL.DIMMABLE LED POWER SUPPLY 250/600mA INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 4 x 0.75mm² 3m
Electrical info	
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI

Remarks

[Click here for SOLI - SHHH 120 acoustic specifications](#)


Options

CABLE BASE R / S

For detailed installation instructions, please consult the manual : [27177_0005_HAND.pdf](#)

COMPATIBLE PARTS

Current supply



203 99 55 CABLE BASE R



DELTALIGHT

SOLI - SHHH PLUS 120/4 LILAC DIM5

21423 0005 B



203 99 56 CABLE BASE S



Electric connection parts




15225 0360 CONNECTION ST




COMPATIBLE LUMINAIRES


SOLISCAPE - 52 SHHH



27187 9020 SOLI - 52 SHHH SOFT 93020



27187 9030 SOLI - 52 SHHH SOFT 93045



27187 9040 SOLI - 52 SHHH SOFT 93030

Notes: