



EN-SUITE R HE OK 93018

26323 9310 B

AVAILABLE IN
BLACK 26323 9310 B
WHITE 26323 9310 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 48
RECESSED DEPTH (MM)	64
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 250mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 4,2W / CRI>90 (R9: 50) / 3000K / 676lm
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	676lm // 4,2W // 161lm/W
LED TECHNICS (LUMINAIRE)	509lm // 4,8W // 105lm/W

Requirements	
LED POWER SUPPLY 250mA-DC DIM (Remote)	

For detailed installation instructions, please consult the manual : [26323_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION






LED power supplies

of Fixtures








of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	3(2)	☐
	Dimtype: 1-10V or push button		
	Cutout dimension (mm): 72		
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	2(2)	☐
	Dimtype: DALI		
	Cutout dimension (mm): 72		
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6)	☐
	Dimtype: 1-10V or DALI or push button		
	Cutout dimension (mm): 84		
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	2->3(2)	☐
	Dimtype: 1-10V or push button		
	Cutout dimension (mm): 55		
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2)	☐
	Dimtype: DALI		
	Cutout dimension (mm): 55		

EN-SUITE R HE OK 93018

26323 9310 B

	21012 0080 LED POWER SUPPLY MULTI POWER 60-360mA-DC Dimtype: non-dimmable Cutout dimension (mm): 40	2 ☐
	21012 0095 LED POWER SUPPLY 250mA-DC / 10W DIM5 Dimtype: DALI Cutout dimension (mm): 40	2 ☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	2 ☐
	21012 0338 LED POWER SUPPLY 250mA / 6W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	1 ☐

Notes: