





## KIX S PIN 24V 93010

13529 9310 N

AVAILABLE IN  
**ANTHRACITE** 13529 9310 N  
**PINE GREEN** 13529 9310 PGR



 [View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Surface mounted
<b>INGRESS PROTECTION</b>	IP65
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK03
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	180° swiveling, 360° rotatable
<b>INFORMATION</b>	LENS 10° INCL.1 x CABLE H05 RN-F 2 x 1 mm <sup>2</sup> 2m EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output)

### Electrical info

<b>ELECTRICAL</b>	24V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm
<b>TM-30 VALUES</b>	rf: 92 / Rg: 99
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L90B10 > 150000
<b>BEAMANGLE</b>	10°
<b>LED TECHNICS (LIGHT SOURCE)</b>	240lm // 2W // 120lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	171lm // 2,3W // 74lm/W

### Requirements

LED POWER SUPPLY 24V-DC

### Options

CBOX  
 IP68 CONNECTION KIT  
 IP68 CONNECTOR 3P

# DELTALIGHT

## KIX S PIN 24V 93010

13529 9310 N

For detailed installation instructions, please consult the manual : [13529\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 89 24 150** LED POWER SUPPLY 24V-DC / 150W

62

Dimtype: non-dimmable

Cutout dimension (mm): 75




**21012 0160** LED POWER SUPPLY 24V-DC / 24W

10

Dimtype: non-dimmable

Cutout dimension (mm): 55




**21012 0171** LED POWER SUPPLY 24V-DC / 60W DIM1

25

Dimtype: 1-10V

Cutout dimension (mm): 61




**21012 0181** LED POWER SUPPLY 24V-DC / 90W DIM1

37

Dimtype: 1-10V

Cutout dimension (mm): 70




**21012 0191** LED POWER SUPPLY 24V-DC / 120W DIM1

50

Dimtype: 1-10V

Cutout dimension (mm): 70

#### Miscellaneous control equipment



**21032 0320** AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)


# DELTALIGHT

## KIX S PIN 24V 93010

13529 9310 N

### Waterproof connection parts


---



**216 12 00** CBOX

Cutout dimension (mm): 142 x 142

---



**216 12 01** IP68 CONNECTION KIT



**216 12 02** IP68 CONNECTOR 3P

Notes: