
DELTALIGHT




MIKALINE L148 927

REFERENCE 30611 9200 B

AVAILABLE IN
NOIR 30611 9200 B
COULEUR OR 30611 9200 GC





View on website

General info	
LOCATION	interieur
INSTALLATION	Plafond Applique,Plafond Suspendu,Mur Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non réglable
INFORMATION	INCL.PLUG-IN-48V CABLE 11cm black EXCL.LED POWER SUPPLY 48V-DC connection max.140W (3A)

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	G
CERTIFICATION	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LEDFLEX 20W / CRI>90 / 2700K /1485lm
LED TECHNICS (LIGHT SOURCE)	1485lm // 20W // 74lm/W
LED TECHNICS (LUMINAIRE)	781lm // 23W // 34lm/W

Requirements

LED POWER SUPPLY 48V-DC (Remote)
POWERBOX 48V-DC PLUG-IN

Options

MIKALINE - JUNCTION / FIXATION
MIKALINE - CABLE SUSPENSION
PLUG-IN 48V CABLE
CONNECTION CLIP 1 x PLUG-IN 48V
CEILING BASE PLUG-IN 48V

For detailed installation instructions, please consult the manual : **30611_XXX0_HAND.pdf**


DELTALIGHT

MIKALINE L148 927


30611 9200 B

FINISH YOUR SPECIFICATION


le cable d'alimentation



30610 0100 PLUG-IN 48V CABLE 11cm black ☐



30610 0110 PLUG-IN 48V CABLE 1,5m black ☐




30610 0120 PLUG-IN 48V CABLE 3m black ☐



30610 0140 B CONNECTION CLIP 1 x PLUG-IN 48V B ☐


Cutout dimension (mm): 51

les alimentations led




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN ☐

Dimtype: non dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN ☐


Dimtype: non dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W ☐

Dimtype: non dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W ☐

Dimtype: non dimmable

Cutout dimension (mm): 40

MIKALINE L148 927


30611 9200 B



21032 0331 LED POWER SUPPLY 48V-DC / 90W DIM1

Dimtype: 1 à 10 V


Cutout dimension (mm): 75



21032 0345 LED POWER SUPPLY 48V-DC / 90W DIM5

Dimtype: DALI


Cutout dimension (mm): 75



30610 0190 POWER ADAPTER 48V-DC / 60W PLUG-IN

Dimtype: non dimmable

Power box



30610 0170 B POWERBOX 48V-DC / 100W PLUG-IN B

Dimtype: non dimmable

les accessoires de suspension



30610 0080 B MIKALINE - CABLE SUSPENSION SINGLE 1,6m B

les accessoires de fixations



30610 0010 C MIKALINE - JUNCTION 2 FLEX SET C



30610 0020 C MIKALINE - JUNCTION 3 FLEX C

DELTALIGHT

MIKALINE L148 927

30611 9200 B




30610 0030 C MIKALINE - JUNCTION 4 FLEX C



30610 0040 C MIKALINE - JUNCTION 2 HINGE C



30610 0050 C MIKALINE - FIXATION SIDE SET C




30610 0060 B MIKALINE - FIXATION SPACER FLEX SET B



30610 0070 C MIKALINE - FIXATION H/V FLEX C



30610 0090 B MIKALINE - FIXATION SPACER SET B



30610 0180 B MIKALINE - SPACER 90° 2 SET B

Bases de plafond



30610 0150 B CEILING BASE 3 x PLUG-IN 48V B



30610 0160 B CEILING BASE 1 x PLUG-IN 48V B

DELTALIGHT

MIKALINE L148 927

30611 9200 B

Notes: