





MIKALINE L148 927

30611 9200 GC

AVAILABLE IN
BLACK 30611 9200 B
GOLD COLOURED 30611 9200 GC



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PLUG-IN-48V CABLE 11cm black EXCL.LED POWER SUPPLY 48V-DC connection max.140W (3A)

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 20W / CRI>90 / 2700K /1485lm
LED TECHNICS (LIGHT SOURCE)	1485lm // 20W // 74lm/W
LED TECHNICS (LUMINAIRE)	781lm // 23W // 34lm/W




Requirements	
LED POWER SUPPLY 48V-DC (Remote)	
POWERBOX 48V-DC PLUG-IN	

Options	
MIKALINE - JUNCTION / FIXATION	
MIKALINE - CABLE SUSPENSION	
PLUG-IN 48V CABLE	
CONNECTION CLIP 1 x PLUG-IN 48V	
CEILING BASE PLUG-IN 48V	





For detailed installation instructions, please consult the manual : **30611_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply

	30610 0100 PLUG-IN 48V CABLE 11cm black	☐
	30610 0110 PLUG-IN 48V CABLE 1,5m black	☐
	30610 0120 PLUG-IN 48V CABLE 3m black	☐
	30610 0140 B CONNECTION CLIP 1 x PLUG-IN 48V B	☐
Cutout dimension (mm): 51		


LED power supplies

	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	☐
Dimtype: non-dimmable		
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	☐
Dimtype: non-dimmable		
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		

DELTALIGHT

MIKALINE L148 927

30611 9200 GC




21032 0331 LED POWER SUPPLY 48V-DC / 90W DIM1

☐

Dimtype: 1-10V

Cutout dimension (mm): 75




21032 0345 LED POWER SUPPLY 48V-DC / 90W DIM5

☐

Dimtype: DALI

Cutout dimension (mm): 75




30610 0190 POWER ADAPTER 48V-DC / 60W PLUG-IN

☐

Dimtype: non-dimmable

Power box



30610 0170 B POWERBOX 48V-DC / 100W PLUG-IN B

☐

Dimtype: non-dimmable

Suspension parts



30610 0080 B MIKALINE - CABLE SUSPENSION SINGLE 1,6m B

☐

Fixation components



30610 0010 C MIKALINE - JUNCTION 2 FLEX SET C

☐



30610 0020 C MIKALINE - JUNCTION 3 FLEX C

☐

DELTALIGHT

MIKALINE L148 927

30611 9200 GC

	30610 0030 C MIKALINE - JUNCTION 4 FLEX C	☐
	30610 0040 C MIKALINE - JUNCTION 2 HINGE C	☐
	30610 0050 C MIKALINE - FIXATION SIDE SET C	☐
	30610 0060 B MIKALINE - FIXATION SPACER FLEX SET B	☐
	30610 0070 C MIKALINE - FIXATION H/V FLEX C	☐
	30610 0090 B MIKALINE - FIXATION SPACER SET B	☐
	30610 0180 B MIKALINE - SPACER 90° 2 SET B	☐

Ceiling bases

	30610 0150 B CEILING BASE 3 x PLUG-IN 48V B	☐
	30610 0160 B CEILING BASE 1 x PLUG-IN 48V B	☐

DELTALIGHT

MIKALINE L148 927

30611 9200 GC

Notes: