DELTALIGHT

DOT.COM L4 ON 93016

REFERENCE 11525 9310 W-B

AVAILABLE IN
BLACK-BLACK 11525 9310 B-B
WHITE-BLACK 11525 9310 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR SP-16° INCL.LED POWER SUPPLY 1050mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 12,6W / CRI>90 (R9: 50) / 3000K / 1226lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
BEAMANGLE	16°
LED TECHNICS (LIGHT SOURCE)	1226lm // 12,6W // 97lm/W
LED TECHNICS (LUMINAIRE)	959lm // 14,5W // 66lm/W

For detailed installation instructions, please consult the manual : **11525_XXX0_HAND.pdf**

Notes:

DOT.COM L4 ON 93016

11525 9310 W-B