



## DEEP RINGO HE 92740

19440 9230 BRAT

AVAILABLE IN

**BLACK** 19440 9230 B

**BRUSHED ALU** 19440 9230 BRA

**BRUSHED ANTHRACITE** 19440 9230 BRAT

**BRUSHED BROWN BRONZE** 19440 9230 BRBB

**BRUSHED COPPER** 19440 9230 BRCU

**BRUSHED GOLD** 19440 9230 BRG

**BRUSHED OLD BRONZE** 19440 9230 BROB

**CREAM** 19440 9230 CR



**FLEMISH BRONZE** 19440 9230 FBR

**FLEMISH GOLD** 19440 9230 FG

**GOLD COLOURED** 19440 9230 GC

**PIANO BLACK** 19440 9230 PB

**WHITE** 19440 9230 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 76
<b>RECESSED DEPTH (MM)</b>	90
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	min.5
<b>INGRESS PROTECTION</b>	IP43/20
<b>WEIGHT (KG)</b>	0.2
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	LENS WFL-40° EXCL.LED POWER SUPPLY 350mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	EPD, LCA

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm
<b>TM-30 VALUES</b>	rf: 96 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	40°
<b>LED TECHNICS (LIGHT SOURCE)</b>	905lm // 6W // 150lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	736lm // 6,9W // 107lm/W

### Remarks

High Efficacy : > 100lm/W

### Requirements

LED POWER SUPPLY 350mA-DC DIM

# DELTALIGHT

## DEEP RINGO HE 92740

19440 9230 BRAT


For detailed installation instructions, please consult the manual : [19440\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

### FINISH YOUR SPECIFICATION

#### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

# DELTALIGHT

## DEEP RINGO HE 92740

19440 9230 BRAT


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 90 91** LED POWER SUPPLY 350mA-DC / 15W

2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 40




**300 90 110** LED POWER SUPPLY 350mA-DC / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42




**300 90 116** LED POWER SUPPLY 350mA-DC / 18W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



**21012 0515** LED POWER SUPPLY MULTI POWER DIM5

1(1)

Dimtype: DALI

Cutout dimension (mm): 55




**21012 0520** LED POWER SUPPLY 350mA-DC / 8W

1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 47



**21012 0575** LED POWER SUPPLY MULTI POWER DIM5

2->3(2)

Dimtype: DALI

Cutout dimension (mm): 55

Notes: