



MULTINOVA 55 930



28011 9300 B

AVAILABLE IN

BLACK 28011 9300 B

GOLD COLOURED 28011 9300 GC

WHITE 28011 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed,Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	4767lm // 34,4W // 139lm/W
LED TECHNICS (LUMINAIRE)	3842lm // 40W // 97lm/W

Options

MULTINOVA 55 SUSPENSION SET
MULTINOVA ROD SUSPENSION
MULTINOVA 55 RECESSED KIT


For detailed installation instructions, please consult the manual : [28011_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	 28010 0050 - MULTINOVA 55 RECESSED KIT Required
 Plasterboard	 28010 0050 - MULTINOVA 55 RECESSED KIT Required
 Stucanet	 28010 0050 - MULTINOVA 55 RECESSED KIT Required
 Concrete + plaster	 28010 0050 - MULTINOVA 55 RECESSED KIT Required
 Lintel + plaster	 28010 0050 - MULTINOVA 55 RECESSED KIT Required
 Hollow-core slab + plaster	 28010 0050 - MULTINOVA 55 RECESSED KIT Required

FINISH YOUR SPECIFICATION

Recessed kits

	28010 0050 MULTINOVA 55 RECESSED KIT ☐
	Cutout dimension (mm): 610

Suspension parts

	27910 0010 B MULTINOVA 55 SUSPENSION SET 5x0,75 3m B ☐
	27910 0010 W MULTINOVA 55 SUSPENSION SET 5x0,75 3m W ☐
	27910 0030 B MULTINOVA 55 ROD SUSPENSION 0,4m B ☐
	27910 0030 W MULTINOVA 55 ROD SUSPENSION 0,4m W ☐

DELTALIGHT

MULTINOVA 55 930

28011 9300 B



27910 0040 B MULTINOVA 55 ROD SUSPENSION 0,8m B

☐

27910 0040 W MULTINOVA 55 ROD SUSPENSION 0,8m W

☐

Notes: