



## SPL14 - SPY 20 93030 DIM5

### REFERENCE

27312 9325 B

### AVAILABLE IN



**BLACK** 27312 9325 B

**FLEMISH BRONZE** 27312 9325 FBR

**FLEMISH GOLD** 27312 9325 FG

**GOLD COLOURED** 27312 9325 GC

**WHITE** 27312 9325 W



[View on website](#)



### General info

|                           |                                                                           |
|---------------------------|---------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                    |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                            |
| <b>INGRESS PROTECTION</b> | IP20                                                                      |
| <b>WEIGHT (KG)</b>        | 0.1                                                                       |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 355° rotatable                                       |
| <b>INFORMATION</b>        | REFLECTOR FL-30°<br>EXCLLED POWER SUPPLY 48V-DC<br>SPY 20 TUBE B included |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | E        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |                                                |
|------------------------------------|------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                            |
| <b>LIGHTSOURCE</b>                 | LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm |
| <b>TM-30 VALUES</b>                | Rf: 91 / Rg: 101                               |
| <b>SDCM</b>                        | SDCM3                                          |
| <b>RISKGROUP</b>                   | RG2                                            |
| <b>LM80</b>                        | L90B10 > 150000                                |
| <b>BEAMANGLE</b>                   | 30°                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 240lm // 2W // 120lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 181lm // 2,3W // 79lm/W                        |

### Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27312\\_XXX5\\_HAND.pdf](#)

## SPL14 - SPY 20 93030 DIM5

27312 9325 B

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

37


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

90

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

37

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

75

Dimtype: non-dimmable

Cutout dimension (mm): 40

### COMPATIBLE COMPOSABLES

#### D-LINER SHIFTLINE 19

#### Available Colours



**29110 0010** D-LINER 19 SL PROFILE SET SAPP 2m




**29110 0030** D-LINER 19 SL PROFILE SET 30BD 2m



#### SPLITLINE 14 profile

#### Available Colours




**27300 0020** SPL14 - PROFILE 2m



# DELTALIGHT

## SPL14 - SPY 20 93030 DIM5

27312 9325 B



**27300 0030** SPL14 - PROFILE 3m



Notes: