





INFORM 40 SQ 320 DOWN-UP 93063 DIM5

30733 9335 B-B

AVAILABLE IN

BLACK-BLACK 30733 9335 B-B

WHITE-BLACK 30733 9335 W-B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver DALI DT6 : DOWN & UP on separate channels INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm UP (HO): LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm Or DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm UP: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm
TM-30 VALUES	Rf: 92 / Rg: 100 DOWN: rf: 92 / Rg: 100 UP: rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 6989lm // 48,4W // 145lm/W UP (HO): 6989lm // 48,4W // 145lm/W Or DOWN: 5069lm // 32,6W // 155lm/W UP: 5069lm // 32,6W // 155lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 4836lm // 55,7W // 87lm/W UP (HO): 4603lm // 55,7W // 83lm/W Or DOWN: 3507lm // 37,5W // 94lm/W UP: 3338lm // 37,5W // 89lm/W

DELTA LIGHT

INFORM 40 SQ 320 DOWN-UP 93063 DIM5

30733 9335 B-B


Options

CABLE BASE R/S

For detailed installation instructions, please consult the manual : [30733_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



Ø57

41

203 99 55 ANO

CABLE BASE R ANO

☐

203 99 55 B

CABLE BASE R B

☐

203 99 55 W

CABLE BASE R W

☐



57

57

41

203 99 56 ANO

CABLE BASE S ANO

☐

203 99 56 B

CABLE BASE S B

☐

203 99 56 W

CABLE BASE S W

☐

Notes:

Delta Light NV may revise the information and technical data at any time without notice. Version: 28/04/2026

2 / 2