

DELTALIGHT



OML50 CT - 48V 200W 2,0m + PRISMATIC LENS D TW 2296mm 950 DIM5

31166 9005 B

AVAILABLE IN
BLACK 31166 9005 B

 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.7
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 42W / CRI>90 (R9: 50) / 2700K-5000K / 5615lm Or @ 5000K: LED cluster 38,4W / CRI>90 (R9: 50) / 2700K-5000K / 6693lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 5615lm // 42W // 134lm/W Or @ 5000K: 6693lm // 38,4W // 174lm/W

Options

WIRELESS CONTROL DIM5

Notes: