


28467 9020 B

Technical drawing of the Ø95 x 126 mm LED downlight. The drawing shows the side profile of the light fixture, which has a diameter of Ø95 mm and a height of 126 mm. A curved arrow indicates the adjustable range of the light head, from 0° to 35°.



Ver en el sitio web



Información de la fuente de luz	
LIGHTSOURCE NAME	LED
FUENTE DE LUZ	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30-15 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
GRUPO DE RIESGO	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
INFORMACIÓN TÉCNICA LED (FUENTE DE LUZ)	979lm // 9W // 109lm/W
INFORMACIÓN TÉCNICA LED (LUMINARIA)	709lm // 10.4W // 68lm/W

MOUNTING KIT ENTERO ROUND M
LED POWER SUPPLY 500mA-DC TW (Remote)

ENTERO M HONEYCOMB
ENTERO M LINEAR SPREAD LENS
ENTERO M SPREAD LENS
ENTERO M SOFTENING LENS
ENTERO M GLASS SBL

Para obtener instrucciones de instalación detalladas, consulte el manual : [28467_XXX0_HAND.pdf](#)

COMPATIBILIDAD CON TECHO

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required
	 28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required


TERMINE SU ESPECIFICACIÓN

Fuente de Alimentación LED

de luminarias

 # de luminarias indica cuántos dispositivos se pueden conectar (min -> max) a la fuente de alimentación. Los valores antes y después del '|' corresponden respectivamente a la corriente de accionamiento mínima y máxima. Los valores entre paréntesis son aplicables a 110V.

Corriente mín. | Corriente máx.



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

Tipo de regulación: con DALI

Dimensión de corte (mm): 85


2

DELTALIGHT

ENTERO RD-M TRIMLESS TW 94030

28467 9020 B

Mounting Kit




28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.

☐

Dimensión de corte (mm): 127

Mounting Kit techo tensado



28400 0080 MOUNTING KIT ENTERO RD-M CSC

☐


28400 0140 MOUNTING KIT ENTERO RD-M WSC

☐

Dispositivos de modificación de Luz




28500 0070 ENTERO M LINEAR SPREAD LENS

☐


28500 0080 ENTERO M SPREAD LENS

☐

28500 0090 ENTERO M SOFTENING LENS

☐

28500 0100 ENTERO M GLASS SBL

☐


28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

☐

DELTALIGHT

ENTERO RD-M TRIMLESS TW 94030

28467 9020 B



28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B

☐

Reflector / lente reemplazable



24611 0220 SPY 66 REFLECTOR 18°

☐



24611 0230 SPY 66 REFLECTOR 30°

☐



24611 0240 SPY 66 REFLECTOR 45°

☐

Notes: