



OML50 CT - 48V 200W 2,5m + PRISMATIC LENS D TW 2624mm 950 DIM5

31167 9005 B

BESCHIKBAAR IN
ZWART 31167 9005 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	4.2
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@ 2700K: LED cluster 48W / CRI>90 (R9: 50) / 2700K-5000K / 6418lm Or @ 5000K: LED cluster 43,9W / CRI>90 (R9: 50) / 2700K-5000K / 7650lm
SDCM	SDCM3
RISK-GROEP	RG1
LED TECHNIEK (LICHTBRON)	@ 2700K: 6418lm // 48W // 134lm/W Or @ 5000K: 7650lm // 43,9W // 174lm/W

Opties

WIRELESS CONTROL DIM5

Notes: